

MTP3000 SERIES SAFER, TOUGHER, EASIER TO USE

PRODUCT SPECIFICATIONS





SAFER

SUPERIOR AUDIO AND INCREASED RANGE

TOUGHER

DURABLE CONNECTORS AND RUGGED DESIGN

EASIER

INTUITIVE HARDWARE AND SOFTWARE FEATURES







	MTP3100	MTP3200	MTP3250
Bluetooth*	No	Yes	Yes
GPS*	No	Yes	Yes
Keypad	Simple	Simple	Full

GENERAL	
Dimensions HxWxD mm	124 x 53 x 33.5 (with standard battery)
Weight	273g (radio with 1650mAH battery and antenna)
Battery Performance (Class 4 and 1650mAH battery)	Duty Cycle 5/5/90 > 16 Hours Duty Cycle 5/35/60 > 12 Hours
Battery (Li Ion 1650mAh and 2150mAh)	

RF SPECIFICATIONS	
Frequency Bands	350-430 MHz
Transmitter RF	Power Class 3L (1.8W) & Class 4 (1W)
Receiver Class	A and B
Rx Static Sensitivity	-114dBm (min); -116dBm (typical)
Rx Dynamic Sensitivity	-105 dBm (min); -107 dBm (typical);

ENVIRONMENTAL SPECIFICATIONS		
Operating Temperature °C	-30 to +60	
Storage Temperature °C	-40 to +85	
Humidity	ETSI 300 019-1-7 class 7.3E	
Dust and Water Ingress Protection	IP65 per IEC 60529	
Shock, drop and vibration	ETSI 300-019 1-7 class 5M3; MIL-STD 810 D/E/F	

LICENSES/OPTIONS	
Efficiency	
Language & Keypad Options	
Bluetooth*	
DMO Repeater	
RUA/RUI*	
MSPD*	
SCCH	
RMS*	
Call Out*	
WAP push*	
Safety	
GPS*	

SECURITY SERVICES	
Enhanced Security - OTAR/DMO SCK*	
Authentication (Mutual)	
Air Interface Encryption Class 1, 2, and 3	
SIM Encryption (MTP3200 / MTP3250 only)	
Permanent Disable*	
Temporary Disable*	

MAIN DATA SERVICES
MSPD*
SDS Messaging in TMO & DMO
AT Commands Full Set of AT Commands (including Voice Control)
Short Data Applications
TNP1 Simultaneous operation of Packet Data and Short Data Services over a common Peripheral Equipment Interface (PEI)
iTM Fleet Management (Remote Programming)

*SW Upgradable

THE KEY BENEFITS OF THE MTP3000 SERIES

STAY IN TOUCH

Be safer and more effective with greater coverage and in-building performance with the high-sensitivity receiver and Class 3L (1.8W) power.

HEAR AND BE HEARD

Outstanding audio means you can be safe and effective in the most noisy and difficult environments.

PRODUCT SPEC SHEET

MTP3000 SERIES

LOCATION SERVICES	
Simultaneous Satellites	12
GPS antenna integrated into the external radio antenna	
Tracking Sensitivity	-160dBm
Accuracy	2 meter (50% probable) @ -130dBm
Protocols	ETSI LIP & Motorola LRRP

USER INTERFACE

Easy to use separate volume and talkgroup knobs

Colour Transflective Display 132x90 pixel screen with 262,144 vivid colours - viewable in bright sunlight

Flip screen and large/x-large text & icon options

Screen Saver gif image & text (any user's selection)

Universal Time Display

Multiple Languages

Keypad Lock

Talkgroup Management User friendly, flexible, efficient, fast

Talkgroups – TMO Folders 256, TMO Unique 2048, TMO Instances 4000

Talkgroups – DMO Folders 128, DMO Groups 1024

Favourite Folders Up to 3 (to store any favourite talkgroup)

Menu Tailored to user needs

Menu Shortcuts

Menu Configuration

Contacts Management Cellular Type (Rapid Search)

Contact List up to 1000 contacts up to 6 numbers per contact, max 2000 numbers

Multiple Dialling Methods user selects how to dial

Fast/Flexible Call Response - Private Call Response to a Group Call via One Touch Button

Multiple Ring Tones

Message Manager Cellular Type (Flexible)

Text message list 20

Intelligent Keypad Text Input (MTP3250)

Status list 400

Country/Network Code List 100

Scan lists 40 lists of 20 groups

User Controls

Multi-Rotary Knob Volume, List Scroll, and/or Talkgroup Selection

(The MTP3000 Series have 2 separate knobs)

One touch Buttons & Keys each button key can be programmed with one of the multiple functions available

Covert Mode

Backlight

MAIN VOICE SERVICES

Full Duplex TMO Private, PABX, PSTN, Emergency

Half Duplex TMO Private, Group, Emergency

Half Duplex DMO Private, Group, Emergency

Inter-MNI, Gateway, Repeater

Dialling Direct, Scroll, Speed, One touch button/key,

AlphaNumeric Search, Call History Redial

Emergency Tactical Emergency Group Call to ATTACHED talkgroup

(tailored by users) Non-Tactical Emergency Group Call to DEDICATED talkgroup $% \left\{ \mathbf{r}_{1}^{\mathbf{r}}\right\} =\mathbf{r}_{2}^{\mathbf{r}}$

Individual Emergency Call to PREDEFINED party (half/full duplex)

HOT MIC talk without need to PTT (user enabled)

Status Msg sent to dispatch console (user enabled)

DMO to TMO enter DMO emergency (with/without gateway)

or enter TMO emergency
Preemptive Priority Calls

Call Out*

PTT Double Push

Adaptive Audio Control

OTHERS

Robust and 'quick connect' side connector with high-performance matching accessories

Robust bottom connector

Loud and clear Audio –

2Wrms Audio power (4W peak) through radio and accessories

SLIM connector Accessories interface

Identification ring on antenna

A full range of matching and high performance accessories are available on the MTP3000 Series Accessory Catalogue by visiting www.motorolasolutions.com/MTP3000

*SW Upgradable

BUILT FOR A TOUGH WORLD

Robust connectors withstand hard use and dirty environments. IP65 for all weather and water jet protection.

PICK IT UP AND USE IT FAST

Transition quickly from analogue radios with two control knobs. Navigate quickly through the simple user interface on the clear screen.

CUSTOMISE FOR THE END USER

Tough and effective range of audio and energy accessories suitable for the same rough use as the radio.



MTP3000 SERIES YOUR LIFELINE WHEN TIME IS CRITICAL

For more information on the MTP3000 Series radio, please visit us on the web at: www.motorolasolutions.com/MTP3000

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2012 Motorola, Inc. All rights reserved. Specifications are subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.



